



Brand: Ranger
Model: R26ST
Description: High Performance Tire Changer

You can now have 26" of external clamping performance without the need for clumsy adapters or cumbersome tabletop adjustments. The fastest and most trouble-free way to service low-profiles, run flats and high-performance alloy wheels. The Model R26ST reduces fatigue and allows technicians to work more efficiently. Perfect for high volume tire shops that service large, low-profile tires.

| FEATURES / SPECIFICATIONS | MODEL R26ST |
|---|---------------------------------|
| Type of Drive System | Electric / Air |
| Motor | 1-1/2 hp (110/220VAC 50-60 HZ) |
| Air Requirement | 110-175 PSI (8-12 BAR) |
| Wheel Clamping Method | 4 Clamps - Internal / External |
| Table Clamping System | Dual Pneumatic Cylinders |
| Bead Breaking System | Pneumatic Blade |
| Tool Holder | Air-Lock Mounting |
| Inflation Gauge With Integrated Air Dump Valve | Standard |
| Inflation Pressure Regulator/Limiter | Standard |
| Water Filter / Oiler / Lubricator / Air Regulator | Standard |
| Breaker Bar | Standard |
| Large Soap / Lubricator Bucket / Brush | Standard |
| Tower Design | Tilt-Back |
| Bead Lifting Roller(s) | Single / Left |
| Traveling Drop-Center Hold Down Devise | Standard |
| Inflation Restraint Devise | Standard |
| Powerful "Jet-Blast" Bead Seating System | Standard |
| Tool Tray / Bin Storage | Standard |
| Internal Rim Clamping Capacity | 14-1/2" – 28" (368 mm - 711 mm) |
| External Rim Clamping Capacity | 12-1/2" – 26" (315 mm - 660 mm) |
| Turntable Tire Width Capacity (Mounting) | 5" – 22" (127 mm – 559 mm) |
| Bead Breaker Tire Width Capacity (Demounting) | 3" – 15" (76 mm – 381 mm) |
| Maximum Tire Diameter | 47" (1194 mm) |
| Shipping Weight | 1025 lbs. (465 Kg) |



Specifications are subject to change without notice.