



An increased cabinet size and larger solution tank makes the RS-500 more versatile and productive. By using an octagonal full-opening door, we've increased access to the turntable allowing operators enhanced loading capabilities. Simple operating controls stainless-steel nozzles, a gasket-free door and a large 70-gpm pump, demonstrate Ranger's commitment to enhance performance and productivity. Like all Ranger spray-wash cabinets, the RS-500 is built to last. We purposely constructed the cabinet and door with heavy-duty 12-gauge steel, then we coated it with an industrial two-step primer and polyurethane finish. All-around performance, durability and improved operator convenience helps make the RS-500 the definitive choice among professionals worldwide.



**Brand: Ranger**  
**Model RS-500 Spray-Wash Cabinet**

Overall Height	66" / 1676 mm
Inside Height	43" / 1092 mm
Inside Width	32" / 813 mm
Turntable Diameter	30" / 762 mm
Recommended Floor Space	44" x 43" / 1118 mm x 1092 mm
Load Capacity	500 lbs. / 227 Kgs.
Cycle Timer	0-60 minutes
Stainless-Steel Nozzles	18
Cabinet / Door Construction	Steel / 12 Gauge / .109 Thickness
Pump Output	75 psi @ 70 gpm
Motor (*)	1-HP / 220 Volt AC / 60 Hz / 1 Phase
Electric Heater	6 Kilowatts
Power Consumption / Pump Only	7 Amps @ 208 Volts / 6.5 Amps @ 230 Volts
Power Consumption / Pump On – Heater On	24 Amps @ 208 Volts / 23 Amps @ 230 Volts
Water Temperature	0° - 190° Fahrenheit
Large Drain Pipe	Standard
Heavy-Duty Rubber Casters	Standard
Tank Capacity	50 Gallons
Removable Tank Screen	Standard
Stainless Oil Skimmer	Standard
Friction-Drive Turntable System	Standard
Full Opening Octagonal Door	Standard
Gasket-Free Door	Standard
Small Parts Basket	Standard
Steam Vent	Optional
Stainless-Steel Handles	Standard
Removable Parts Tree	Standard
25 pounds Detergent	Standard
Shipping Weight	740 lbs. / 336 Kg.